

# Homogenizer HLI75

- Max. 20.000 Liter per hour
- Homogenizing pressure up to 700 bar
- Absorbed motor power: max. 75 kW
- Optional in aseptic execution
- Poppet valves for low viscous and slight abrasive products
- Ball valve for high viscous and abrasive products
- Integrated lubrication system
- Best ecological footprint

*Weight incl. motor: max. 2.650 kg  
Technical changes reserved*

## Poppet valves

Poppet valves for low viscous and slight abrasive products

Model	Max. Pressure	Max. Capacity
HLI75	(bar / psi)	(l/h / gpm)
-100T	100 / 1,450	20,000 / 88
-150T	150 / 2,175	14,000 / 62
-200T	200 / 2,900	10,500 / 46
-250T	250 / 3,600	8,500 / 37
-300T	300 / 4,350	7,000 / 31
-350T	350 / 5,075	6,000 / 26
-550T	550 / 7,975	3,800 / 17

## Ball valves

For abrasive and high viscous products

Model	Max. Pressure	Max. Capacity
HLI75	(bar / psi)	(l/h / gpm)
-150K	150 / 2,175	14,000 / 62
-200K	200 / 2,900	10,500 / 46
-250K	250 / 3,600	8,200 / 36
-350K	350 / 4,350	5,900 / 25
-550K	550 / 5,075	3,700 / 16
-700K	700 / 10,000	2,900 / 13

